



SERIES: DIVA 2

MODEL NO.

NDV3 = 2.4W Length 7.59" (193mm)
NDV4 = 3.5W Length 11.2" (285mm)
NDV7 = 7W Length 22.24" (565mm)
NDV11 = 10.5W Length 33.27" (845mm)

T

COLOR / K

27K = 2700K*
30K = 3000K*
35K = 3500K
40K = 4000K*
65K = 6500K
 *Quickship

VOLTAGE

24V = DC24V
 Standard

DIMENSIONS

Model No.	Power Input	Lamp Power	A	B	C
NDV3	DC24V	2.4W	7.4"	7.59"	8.26"
NDV4	DC24V	3.5W	11.02"	11.22"	11.88"
NDV7	DC24V	7W	21.96"	22.24"	22.80"
NDV11	DC24V	10.5W	33.00"	33.27"	33.84"

Product Features

- Dark spot free at the linking point
- Eco friendly product
- Super slim sizes
- Various mounting methods
- Ultra slim profile
- Snap together connecting system
- Magnetic and bracket mounting methods

Specifications

- Voltage: DC24V
- Operating temperature: 0°-45°C / 32°-104°F
- Lamp life: 40,000 hours
- Available color: 2700K, 3000K, 3500K, 4000K, 6500K
- Color Rendering Index (CRI) = Ra > 80
- Class Protection: II
- Degree of Protection: IP20
- 70 lumens per watt

Warranty

3 year warranty

Certifications



Beam Angle

120°

Mounting

NDV1 = Bracket (Standard) * ships with fixture
NDV2 = 15 / 45 degree mounting

Finish

Anodized aluminum finish (Standard)

Weight

NDV3 = 0.01 lb.
NDV4 = 0.015 lb.
NDV7 = 0.02 lb.
NDV11 = 0.04 lb.

POWER SUPPLY & ACCESSORIES(PS)

DIVA2 power consumption is 65lm/W (maximum run length 55W'). DIVA2 operates on DC 24V using a selection of 3 LED converters for 15W, 30W and 75W with a 6-way distributor and power cord.

DIMMING

Optional low voltage 0 - 10 dimming interface available. Refer to Driver Spec Sheets.

LED DRIVERS

- ___ FLC15-24V/XL
- ___ FLC30-24V/XL
- ___ FLC75-24V/XL

Refer to Power Supply (PS) Spec Sheets to order.

CONNECTORS

- ___ NDVPTC = 6"
- ___ NDVPTC1 = 1'
- ___ NDVPTC2 = 2'
- ___ NDVPTC4 = 4'
- ___ NDVPTC6 = 6'

POWER CORD

- ___ NDVPC

TOTAL RUN LENGTH:

DIVA2 offered in 4 lengths starting at 8".
 EX: 10' = 10' RUN
 or
 Utilize Preconfigured Run Length Order Code (Refer to submittals)
 or
 To Be Determined (TBD)
 when run length is unknown

PRODUCT SPECIFICATION EXAMPLE:

NDV3	T	27K	24V		
MODEL		COLOR/K	VOLTAGE	RUN LENGTH	REQUIRED POWER SUPPLY & ACCESSORIES* *see Submittal Sheets