







Nominal 1' - 5W

Nominal 2' - 10W

Nominal 3' - 15W

∄ 5/16"

7/8"

Nominal 4' - 20W

Mounting

MSL

SL-Bracket 1 BRACKET 1: 45°

SL-Bracket 2 BRACKET 2: 90°

MSL-BRACKET: 180° MSL-BRACKET: 90° *









*ships w/ fixture

Product Features

- AC power with integral driver
- Transparent, ivory white diffuser (clear cover available upon request)
- Isolation circuit applied
- Compatible with accessories for fluorescent SlimLamp

Specification

- Frequency range: 60Hz
- Voltage: 120V
- Color Rendering Index (CRI) = Ra > 80
- Lamp Life 40,000 hrs @ 70% output
- Tube diameter: 16mm (T5) - Class of protection: I
- Degree of protection: IP20
- Operating Temperature: 0-50°C

32-113°F

Beam Angle

120° = LSL

Notice

Max connection: 400W 5W(80pcs), 10W(40pcs), 15W(26pcs), 20W(20pcs)

Finish

Anondized aluminum finish (Standard)

Weight (w/ lamp and cover)

LSL 5W = .50 lb.

LSL 10W = .80 lb.

LSL 15W = 1.25 lbs.

LSL 20W = 1.50 lbs.

MODEL NO.

LSL 5W = 5W Length 1' (305mm) **LSL 10W** = 10W Length 2' (610mm) **LSL 15W** = 15W Length 3' (914mm)

LSL 20W = 20W Length 4' (1219mm)

COLOR / K

27K = 2700K

30K = 3000K*

35K = 3500K

40K = 4000K*

65K = 6500K

*Quickship

VOLTAGE

120V = 120 volts

MOUNTING

MSL = Metal Bracket (ships with fixture) **SL-Bracket1** = 45° Mounting Bracket SL-Bracket2 = 90° Mounting Bracket

Warranty

3 year warranty

Certifications













POWER SUPPLY & ACCESORIES (PS)

Can be powered by standard 120V cord and plug or Feelux Supplied Metal Hard Wire Box

PRODUCT SPECIFICATION EXAMPLE:

LSL_10W 30K 120V SL Bracket1 STD MODEL COLOR/K VOLTAGE MOUNT REOUIRED POWER SUPPLY & ACCESSORIES*

*see Submittal Sheets

Accessories

CONNECTORS

DLCPL/XL = Direct Connector

DLPTC/XL = Connecting cable 6" (150mm)

DLPTC1/XL = Connecting cable 1' (300mm)

_DLPTC1/XL = Connecting cable 1 (300mm)
_DLPTC2/XL = Connecting cable 2' (600mm)
_DLPTC4/XL = Connecting cable 4' (1200mm)
_DLPTC6/XL = Connecting cable 6' (1800 mm)

POWER CORD

 $_{\mathbf{DLPC120/XL}} = Power cord 6' (1800mm)$ with plug

DLPC120/SM2 = Power cord 6' (1800mm) with straight connector

_MHWB/XL = Metal hard wire box

*Other connector lengths available on request.