

**MODEL NO.**

NSL\_8W = 8W Length 1.95' (595mm)  
 NSL\_14W = 14W Length 2.9' (895mm)  
 NSL\_21W = 21W Length 3.92' (1195mm)  
 NSL\_28W = 28W Length 4' (101.6mm)  
 NSL\_35W = 35W Length 5' (127mm)

**COLOR / K**

22K = 2200K  
 27K = 2700K  
 30K = 3000K  
 35K = 3500K  
 40K = 4000K  
 65K = 6500K  
 80K = 8000K

**VOLTAGE**

120V = 120 volts

**OPTIONS**

C = Cover (Polycarbonate diffuser)

**MOUNTING**

MSL = Metal Bracket (ships with fixture)  
 SL-Bracket1 = 45 ° Mounting Bracket  
 SL-Bracket2 = 90 ° Mounting Bracket



**Mounting**

MSL

SL-Bracket 1

SL-Bracket 2

MSL-BRACKET: 180° MSL-BRACKET: 90° \*

BRACKET 1: 45°

BRACKET 2: 90°



\*ships w/ fixture

**Product Features**

- Linear T5 FL (Linkable) Undercabinet Lighting
- Rigid aluminum extruded body and snap-in mounting brackets
- Cool operation ideal for heat-sensitive item displays
- End of Lamp Life (EOL) protection
- Polycarbonate diffuser gives off a soft glow
- Program start, quiet and flicker free ballast

**Specification**

- Frequency range: 60Hz
- Voltage: 120V
- Power factor: > 97%
- Color Rendering Index (CRI) = RA > 82+
- Lamp life: 20,000hr
- Tube diameter: 16mm(T5)
- Class of protection: I
- Degree of protection: IP20
- Operating Temperature: 0-45 °C  
32-113 °F

**Beam Angle**

240 ° = NSL

**Notice**

Max connection : 600W  
 8W (75pcs), 14W (42pcs), 21W (28pcs),  
 28W (21pcs), 35W (17pcs)

**Finish**

White powder coated finish (Standard)

**Weight (w/ lamp and cover)**

NSL\_8W = .75 lb.  
 NSL\_14W = 1 lb.  
 NSL\_21W = 1.5 lbs.  
 NSL\_28W = 1.8 lbs.  
 NSL\_35W = 2 lbs.

**Shipment**

SlimLamp Kits (fixture, lamps, options) ship assembled unless otherwise specified

**Warranty**

3 year warranty

**Certifications**



**POWER SUPPLY & ACCESSORIES (PS)**

Can be powered by standard 120V cord and plug or Feelux Supplied Metal Hard Wire Box

**DIMMING**

Refer to DimSlimLamp Data Sheets.

**Accessories**

**CONNECTORS**

- \_\_ DLCPL/XL = Direct Connector
- \_\_ DLPTC/XL = Connecting cable 6' (150mm)
- \_\_ DLPTC1/XL = Connecting cable 1' (300mm)
- \_\_ DLPTC2/XL = Connecting cable 2' (600mm)
- \_\_ DLPTC4/XL = Connecting cable 4' (1200mm)
- \_\_ DLPTC6/XL = Connecting cable 6' (1800mm)

**POWER CORD**

- \_\_ DLPC120/XL = Power cord 6' (1800mm) with plug
- \_\_ DLPC120/SM2 = Power cord 6' (1800mm) with straight connector
- \_\_ MHWB/XL = Metal hard wire box
- \_\_ DLSB/XL = On/Off Switch

Other connector lengths available on request.

**PRODUCT SPECIFICATION EXAMPLE:**

NSL_14W	22K	120V	C	SL Bracket1	
MODEL	COLOR/K	VOLTAGE	OPTIONS	MOUNT	REQUIRED POWER SUPPLY & ACCESSORIES* *see Submittal Sheets