


**Mounting**

MSLL  
MSLL-BRACKET



\*ships w/ fixture



**Product Features**

- High efficiency built-in program start ballast
- End of Lamp Life (EOL) protection
- **Low profile rigid extruded aluminum body**
- Quick connection system
- Daisy chain up to 600W together

**Specification**

- Frequency range: 60Hz
- Voltage: 110 -130V  
277V\* HE only
- Power factor: > 97%
- Color Rendering Index (CRI) = Ra > 80
- Lamp life: 20,000hr
- Tube diameter: 16mm(T5)
- Class of protection: I
- Degree of protection: IP20
- Operating Temperature: 0-45 °C  
32-113 °F

**Warranty**

3 year warranty

**Certifications**



**Beam Angle**

270° = NSLL

**Notice**

Max connection : 600W  
14W HE (42 pcs) , 21W HE (28 pcs),  
28W HE (21 pcs), 24W HO (25 pcs),  
39W HO (15 pcs), 54W HO (11 pcs)

**Finish**

White powder coated finish (Standard)

**Weight**

NSLL 14/24W= 1.0 lbs.  
NSLL 21/39W= 1.2 lbs.  
NSLL 28/54W= 1.6 lbs.

**Shipment**

SlimLine Kits (fixture, lamps, options)  
do NOT ship assembled

**POWER SUPPLY & ACCESSORIES (PS)**

Maximum run length 600W. It can be powered by standard 120V cord and plug or Feelux supplied metal hard wire box

**DIMMING**

Refer to DimSlimLine Data Sheets (DSLL)

**MODEL NO.**

- NSLL\_14W = HE 14W Length 22 7/8" (582 mm)\*
- NSLL\_21W = HE 21W Length 34 11/16" (882 mm)\*
- NSLL\_28W = HE 28W Length 46 4/8" (1182 mm)\*
- NSLL\_24W = HO 24W Length 22 7/8" (582 mm)
- NSLL\_39W = HO 39W Length 34 11/16" (882 mm)
- NSLL\_54W = HO 54W Length 46 4/8" (1182 mm)

**COLOR / K**

- 22K = 2200K
- 24K = 2400K
- 27K = 2700K
- 30K = 3000K
- 35K = 3500K
- 40K = 4000K
- 65K = 6500K
- 80K = 8000K

**VOLTAGE**

- 120V = 120 volts
- 277V = 277 volts\* (only available in HE)

**OPTIONS**

- C = Cover (Polycarbonate diffuser)
- SLL14CV = Cover for 4/24W
- SLL21CV = Cover for 21/39W
- SLL28CV = Cover for 28/54W

**Accessories**

**CONNECTORS**

- \_\_SLLCPL/XL = Direct connecting cap
- \_\_SLL-OUTLET CAP = Protecting cap for termination

Connecting Cable from fixture to fixture...

- \_\_SLLPTC/XL = Connecting cable 6" (150mm)
- \_\_SLLPTC1/XL = Connecting cable 1' (300mm)
- \_\_SLLPTC2/XL = Connecting cable 2' (600mm)
- \_\_SLLPTC4/XL = Connecting cable 4' (1200mm)
- \_\_SLLPTC6/XL = Connecting cable 6' (1800mm)

Connecting Cable from Metal Hard Wire Box (MHWB) to first fixture...

- \_\_ESLSLLPTC/XL = Connecting cable 6" (150mm)
- \_\_ESLSLLPTC1/XL = Connecting cable 1' (300mm)
- \_\_ESLSLLPTC2/XL = Connecting cable 2' (600mm)
- \_\_ESLSLLPTC4/XL = Connecting cable 4' (1200mm)
- \_\_ESLSLLPTC6/XL = Connecting cable 6' (1800mm)

**POWER CORD**

- \_\_SLLPC120/XL = Power cord 6' (1800mm) with plug
- \_\_MHWB/DSL = Metal hard wire box

Other connector lengths available upon request

**PRODUCT SPECIFICATION EXAMPLE:**

NSLL_14W	22K	120V	C	STD	
MODEL	COLOR/K	VOLTAGE	OPTIONS	FINISH	REQUIRED POWER SUPPLY & ACCESSORIES*