

FLX Stix NDPro

LED for display, cabinet, furniture & cove

Linear perfection with NDPro



Product Features

- Super Slim Profile
- Close Pitch & Spot Free
- Seamless Lighting
- Perfected with Color Consistency

Specification


- Voltage : DC 24V
- Operating temperature : 0~45° C
- Lamp life : 50,000hr/70%
- Available color : 2700K, 3000K, 3500K, 4000K
- Color rendering : Ra > 85
- Energy efficiency : 90lm/W
- Degree of protection : IP20



DESIGN **PLUS**


light+building
March 2016 in Frankfurt

Magnet



LED SPOT

SPOT-FREE WITH NDPro





FLX Stix NDPro


Standard Output



FLX Stix NDP 1W (3 15/16")



FLX Stix NDP 3W (7 5/8")



FLX Stix NDP 4W (11 1/4")



FLX Stix NDP 7W (22 1/4")




FLX Stix NDP 11W (33 7/32")



FLX Stix NDP 15W (44 7/32")

Various options




Easy connection




Dimension

* Fixture




* LED Converter



Model Name	Power Input (V)	Lamp Power (W)	A (in)	B (in)	C (in)	D (in)	E (in)	F (in)	G (in)
NDP1 40K-24V	DC 24	1	3 3/4	3 15/16	4 13/16	15/32	7/16	13/32	3/8
NDP3 40K-24V	DC 24	3	7 13/32	7 5/8	8 1/2	15/32	7/16	13/32	3/8
NDP4 40K-24V	DC 24	4	11 1/32	11 1/4	12 1/8	15/32	7/16	13/32	3/8
NDP7 40K-24V	DC 24	7	22 1/32	22 1/4	23 3/8	15/32	7/16	13/32	3/8
NDP11 40K-24V	DC 24	11	33 1/32	33 7/32	34 3/32	15/32	7/16	13/32	3/8
NDP15 40K-24V	DC 24	14	44 1/32	44 7/32	45 3/32	15/32	7/16	13/32	3/8

Model name	A (in)	B (in)	C (in)
FLC30-24V/XL	5 29/32	1 5/8	1 7/32
FLC75-24V/XL	7 3/32	2 3/8	1 1/4

Installation




Max. connection

- 55W in one row (single powerfeed)
- LED Driver

LED Driver	Max. units for LED Driver			
	24V/15W	24V/30W	24V/75W	24V/200W
NDP1 40K-24V	12	25	62	160
NDP3 40K-24V	5	10	25	66
NDP4 40K-24V	4	7	18	50
NDP7 40K-24V	2	4	10	28
NDP11 40K-24V	1	2	6	18
NDP15 40K-24V	1	2	5	13

Accessories




(a) Connecting cables(between FLX Stix NDPro & FLX Stix NDPro)

NDPPTC	NDPPTC1	NDPPTC2	NDPPTC4	NDPPTC6
150mm(6inch)	300mm(1feet)	600mm(2feet)	1200mm(4feet)	1800mm(6feet)



(b) Power cable : NDPPC

Power cable (Between FLX Stix NDPro & 6-way distributor)



(c) Mounting bracket : NDP-BRACKET 1

Included in fixture




(d) Angle bracket (15° & 40°) : NDP-BRACKET 2



(e) Sidefeed for seamless extension (3W) : NDP3 40K-24V-S

The dimension is the same as NDP3 40K-24V

Powered only through cable, no power supply on the input connector



(f) End cap : NDP-CAP

Included in fixture



(g) LED Driver with 6way distributor, with power cord (1800mm)

Part No	FLC30-24V/XL	FLC75-24V/XL
Capacity	30W 24V	75W 24V



(h) LED Driver : XLD75-124V-FC

75W 24V hardwire driver compatible with 120/277 primary voltage



(i) Dimming Interface (1-10V) : FDC-L10


Max. 100W (100W/CH, 1CH)



(j) Dimming Interface(0-10/1-10,DMX512)

FDA-L2M0 : Max. 200W (100W/CH, 2CH)

FDA-L5M : Max. 200W (100W/CH, 5CH)



(k) Inline dimmer : NDPDIM (Max 55W in a row)



(l) Door and motion detection sensor : FLS-M24V

Voltage : DC 24V



(m) Human-body detection sensor : FLS-P24V

Voltage : DC 24V