



Mounting

MDL

MDL-BRACKET: 180°
MDL-BRACKET: 90° *

DL-Bracket 1

BRACKET 1: 45°

DL-Bracket 2

BRACKET 2: 90°



*ships w/ fixture



Product Features

- Linear T4 FL (Linkable) Undercabinet Lighting
- Rigid aluminum extruded body and snap-in mounting brackets
- Cool operation ideal for heat-sensitive item displays
- Polycarbonate diffuser gives off a soft glow
- instant start, quiet and flicker free

Specification

- Frequency range: 60Hz
- Voltage: 120V
- Power factor: > 97%
- Color Rendering Index (CRI) = RA > 82+
- Lamp life: 12,000hr
- Tube diameter: 13mm(T4)
- Class of protection: I
- Degree of protection: IP20
- Operating Temperature: 0-45 °C
32-113 °F

Beam Angle

240° = NDL

Notice

Max connection : 270W

Finish

White powder coated finish (Standard)

Weight (w/ lamp and cover)

NDL_7W = 0.02 lbs.
NDL_10W = 0.04 lbs.
NDL_18W = 0.06 lbs.

Shipment

DecoLamp Kits (fixture, lamps, options)
ship assembled unless otherwise specified

MODEL NO.

NDL_7W = 7W Length 10 5/16" (262mm)
NDL_10W = 10W Length 13 6/16" (339mm)
NDL_18W = 18W Length 20 6/16" (517mm)

COLOR / K

27K = 2700K
30K = 3000K
35K = 3500K
40K = 4000K
65K = 6500K
80K = 8000K

VOLTAGE

120V = 120 volts

OPTIONS

C = Cover (Polycarbonate diffuser)

MOUNTING

MDL = Metal Bracket (ships with fixture)
DL-Bracket1= 45° Mounting Bracket
DL-Bracket2= 90° Mounting Bracket

Warranty

1 year warranty

Certifications



POWER SUPPLY & ACCESSORIES (PS)

Can be powered by standard 120V cord and plug or Feelux Supplied Metal Hard Wire Box

Accessories

CONNECTORS

- __ DLPC1/XL = Direct Connector
- __ DLPTC/XL = Connecting cable 6" (150mm)
- __ DLPTC1/XL = Connecting cable 1' (300mm)
- __ DLPTC2/XL = Connecting cable 2' (600mm)
- __ DLPTC4/XL = Connecting cable 4' (1200mm)
- __ DLPTC6/XL = Connecting cable 6' (1800mm)

POWER OPTIONS

- __ DLPC120/XL = Power cord 6' (1800mm) with plug
- __ DLPC120/SM2 = Power cord 6' (1800mm) with straight connector
- __ MHWB/XL = Metal hard wire box
- __ DLSB/XL = On/Off Switch

Other connector lengths available on request.

PRODUCT SPECIFICATION EXAMPLE:

NDL_10W	22K	120V	C	MDL	
MODEL	COLOR/K	VOLTAGE	OPTIONS	MOUNT	REQUIRED POWER SUPPLY & ACCESSORIES* *see Submittal Sheets