




Nominal 1' - 5W

Nominal 2' - 10W

Nominal 3' - 15W

Nominal 4' - 20W



Mounting

MSL

SL-Bracket 1

SL-Bracket 2

MSL-BRACKET: 180° MSL-BRACKET: 90° *

BRACKET 1: 45°

BRACKET 2: 90°



*ships w/ fixture



Product Features

- AC power with integral driver
- Transparent, ivory white diffuser (clear cover available upon request)
- Isolation circuit applied
- Compatible with accessories for fluorescent SlimLamp

Beam Angle

120° = LSL

Notice

Max connection : 400W
5W(80pcs), 10W(40pcs), 15W(26pcs), 20W(20pcs)

Specification

- Frequency range: 60Hz
- Voltage: 120V
- Color Rendering Index (CRI) = Ra > 80
- Lamp Life 40,000 hrs @ 70% output
- Tube diameter: 16mm (T5)
- Class of protection: I
- Degree of protection: IP20
- Operating Temperature: 0-50°C
32-113°F

Finish

Anodized aluminum finish (Standard)

Weight (w/ lamp and cover)

LSL 5W = .50 lb.
LSL 10W = .80 lb.
LSL 15W = 1.25 lbs.
LSL 20W = 1.50 lbs.

Warranty

3 year warranty

Certifications



POWER SUPPLY & ACCESORIES (PS)
SlimLamp LED power consumption is 65 lm/W (maximum run length 400W). Can be powered by standard 120V cord and plug or Feelux Supplied Metal Hard Wire Box

PRODUCT SPECIFICATION EXAMPLE:

LSL_10W	30K	120V	SL Bracket1	STD
MODEL	COLOR/K	VOLTAGE	MOUNT	REQUIRED POWER SUPPLY & ACCESSORIES* *see Submittal Sheets

MODEL NO.

LSL 5W = 5W Length 1' (305mm)
LSL 10W = 10W Length 2' (610mm)
LSL 15W = 15W Length 3' (914mm)
LSL 20W = 20W Length 4' (1219mm)

COLOR / K

27K = 2700K
30K = 3000K*
35K = 3500K
40K = 4000K*
65K = 6500K
*Quickship

VOLTAGE

120V = 120 volts

MOUNTING

MSL = Metal Bracket (ships with fixture)
SL-Bracket1= 45° Mounting Bracket
SL-Bracket2= 90° Mounting Bracket

Accessories

CONNECTORS

- ___DLCPL/XL = Direct Connector
- ___DLPTC/XL = Connecting cable 6' (150mm)
- ___DLPTC1/XL = Connecting cable 1' (300mm)
- ___DLPTC2/XL = Connecting cable 2' (600mm)
- ___DLPTC4/XL = Connecting cable 4' (1200mm)
- ___DLPTC6/XL = Connecting cable 6' (1800mm)

POWER CORD

- ___DLPC120/XL = Power cord 6' (1800mm) with plug
- ___DLPC120/SM2 = Power cord 6' (1800mm) with straight connector
- ___MHWB/XL = Metal hard wire box

*Other connector lengths available on request.